

Product Code:

Product Range:

Issue Date:

Heavy Duty Accessories, Ladder Rack, Heavy Duty

3/12/2025

Description:

HDL/C/G

Heavy Duty Ladder Coupler (Pairs) HDG

Features:

- Couplers are used for joining together straight lengths of ladder together.
- · All fittings in this range have integral couplers.
- Even when ladders are cut to length, the slots in the coupler will always align with the slots in the ladder side rail.
- · Supplied in pairs with the appropriate quantity of fasteners. (4 per coupler)
- Manufactured from the same HDG steel as straight lengths for consistent strength and corrosion protection.



Technical:

Product Type Coupler
Width 13mm
Height 119mm
Length 220mm
Weight 1.00 Kgs
Gauge 1.5mm
Material Post Hot-Dipped Galvanised (HDG)
Colour/Finish Self Colour
Standards BS EN ISO 1461:2009
Supplied With 8x M10 Fastener Sets Per Coupler
Pack Quantity Pairs


Important:

HDG ladders are suitable for internal and external use, including light industrial and coastal environments. Ensure cut edges or drilled holes are treated with a suitable zincrich paint or similar to maintain corrosion protection.

Extra Information

adjust each coupler position to align the slots with the side rail slots and secure with all fasteners.Recommended Torque (M10): 40Nm., Slide the couplers under the return flanges of one ladder side rail and loosely fit a single fastener to each coupler to hold it in place. Slide the second ladder over both couplers

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk