

Product Code: Product Range:

Issue Date:

2/9/2025

Hot Dipped Galvanised, Ladder,

MDL/900/G Medium Duty

Description:

900mm Medium Duty 100mm Deep Ladder HDG - 3 Metre Length

Features:

- Durable hot dip galvanised finish for long-term corrosion resistance.
- Designed to support high cable loads over long spans.
- Suitable for heavy-duty industrial and commercial applications.
- · Wide range of accessories including bends, tees, risers and reducers.
- · Compatible with industry-standard fixings and couplers.
- · Rung spacing: 300mm between centres.
- Even when ladders are cut to length, the slots in the coupler will always align with the slots in the ladder side rails.
- When connecting fittings to straight lengths, use fastener sets.
- Manufactured to meet UK and international standards.
- Covers for cable ladder available upon request.
- 6 metre lengths available upon request.



Technical:

Product Type Ladder Tray Width 900mm Height 100mm Length 3000mm Weight 22.20 Kgs Dimensions 300mm Rung Pitch Gauge 1.5mm Material Post Hot-Dipped Galvanised (HDG) Colour/Finish Self Colour

Important:

HDG ladders are suitable for internal and external use, including light industrial and coastal environments. Ensure cut edges or drilled holes are treated with a suitable zincrich paint or similar to maintain corrosion protection.

Extra Information

Standards BS EN ISO 1461:2009

3 m and 4 m spans using 3 m lengths. Safe working load should include all cable loads and any other additional loads (e.g. wind, snow).

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions: (mm)

W 940mm

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk