

Product Code: Product Range:

Modular Screed Trunking

20/10/2025

Issue Date:

Description:

FSJM350

3 Compartment Intersection for 350x65mm Modular Flush Screed Trunking

Features:

- Intersection to be used as flat bend, tee and fourway.
- Intersections are 65mm deep to allow the maximum cable capacity throughout the system.
- · Reinforced lid to allow foot traffic.
- · Fillets have rubber gasket strip fitted to increase stability and reduce lid deflection.
- Intersections should be installed when the trunking is installed.
- · Screed trunking must be installed on a solid foundation and completely supported by a screed ribbon.



Screed trunking must be installed on a solid

foundation and completely supported across its

Technical:

Product Type Flush Screed Floor Trunking Width 350mm Weight 6.50 Kgs **Number of Compartments**

Material Pre-Galvanised Steel (Zinc Coated) Colour/Finish Self Colour

Standards BS EN 10346:2015

complete width by a screed ribbon.

Important:

Extra Information

The galvanised trunking lids and service boxes should be in position before the screed is poured to ensure the pressure of the screed does not distort the side walls of the trunking.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk