Tamlex Data Sheet



Product Code:

Product Range:

Issue Date:

CSB/3/S

Service Boxes, 3 Compartment Boxes

26/8/2025

Description:

3 Compartment 68mm Deep Cavity Service Box

Features:

- 3 Compartment Cavity Service Box.
- 20mm Knockouts.
- · Reversible self-closing lid.
- Reinforced with steel plates with a recessed lid to allow 10mm infill.
- Durable polycarbonate trim and lid as standard.
- Cable outlets with sponge foam to prevent ingress.
- Floor Cut-out size: 305mm x 205mm.
- Accepts standard 85mm plates only.
- Alternative metal trims available designed specifically for high traffic environments such as receptions and universities. (Can be powder coated).
- Service boxes are designed for use in office type environments and should not be installed in main walkways, corridors, gangways.
- · Not suitable for wheeled traffic areas.
- Customer Notice 68mm depth service boxes have restrictive cable capacity.
- The 68mm cavity and screeded service boxes should only be fitted with flush / panel mounted sockets (C2GS) due to the limited depth.



Technical:

Product Type Cavity Floor Box

Width 225mm

Depth 68mm

Length 320mm

Weight 2.50 Kgs

Dimensions Overall Size: (L) 320mm x (W) 225mm Floor Cut-Out Size: (L) 305mm x (W) 205mm

Number of Compartments

Material Pre-Galvanised Steel (Zinc Coated) / Polycarbonate

Colour/Finish Self Colour

Supplied With 20mm Knockout Only

Extra Information

only flush or panel-mounted sockets (C2GS) should be used.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions: (mm)

W 205mm

L 305mm

Important:

68mm deep service boxes have limited cable capacity.



T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk