

Product Code:

Product Range:

. Duty Assessmine Het

Issue Date: 2/9/2025

HFW/150/300/G Heavy Duty Accessories, Hot Dipped Galvanised, Ladder

Description:

150mm 4 Way Crosspiece R300 For Heavy Duty Ladder HDG

Features:

- Manufactured from the same HDG steel as straight lengths for consistent strength and corrosion protection.
- Designed to maintain uniform rung spacing and alignment throughout changes in direction.
- Precision-formed profiles ensure accurate fit with adjacent components.
- · All fittings have integral coupling tabs and fishplates.
- Internal and external radius options available to suit different bend requirements.
- Ideal for routing around structural obstacles or changing cable direction cleanly.



Technical:


Standards BS EN ISO 1461:2009

Product Type Fourway Width 150mm Height 120mm Weight 8.90 Kgs Diameter 300mm Radius Gauge 1.5mm Material Post Hot-Dipped Galvanised (HDG) Colour/Finish Self Colour

Important:

HDG ladders are suitable for internal and external use, including light industrial and coastal environments. Ensure cut edges or drilled holes are treated with a suitable zincrich paint or similar to maintain corrosion protection.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk