



Product Code:

Perimeter Trunking, Skirting

Product Range:

Issue Date: 25/11/2025

TSK6TSS/G Trunking

Description:

150mm x 60mm Chamfered Skirting 2 Gang Switched Socket

Features:

- o The Tamlex perimeter trunking system offers the end user a quick and easy to fit system.
- o This range combines excellent screening capability and clean design with superior mechanical strength, making it the ideal solution for high traffic environments such as hospitals, laboratories and universities whilst also offering first class fire protection.
- o All metal construction for maximum strength and durability.
- o The dividers are provided with 20mm knockouts every 100mm for easy access between partitions
- o All surface lid are supplied self colour but a wide variety of colours are available for that high quality finish.
- o The powder coating not only offers an attractive finish but is also highly resilient to damage during use and installation.
- o The lid is also available in a self-colour galvanised finish for that more industrial look if required or where on-site coating is required
- o Powder coating is low smoke zero halogen
- o Full range of accessories Cat6a
- The Tamlex perimeter trunking system offers the end user a quick and easy to fit system.
- This range combines excellent screening capability and clean design with superior mechanical strength, making it the ideal solution for high traffic environments such as hospitals, laboratories and universities whilst also offering first class fire protection.
- · All metal construction for maximum strength and
- The dividers are provided with 20mm knock-outs every 100mm for easy access between partitions
- All surface lid are supplied self colour but a wide variety of colours are available for that high quality finish.
- The powder coating not only offers an attractive finish but is also highly resilient to damage during use and installation.
- The lid is also available in a self-colour galvanised finish for that more industrial look if required or where on-site coating is required
- · Powder coating is low smoke zero halogen
- Full range of accessories Cat6a



Technical: Product Type Plates Depth 60mm Height 150mm Weight 0.75 Kgs Number of Gangs 2 Gauge 1.0mm Material Pre-Galvanised Steel (Zinc Coated) Colour/Finish Self Colour Standards BS EN 10346:2015 Supplied With Bridge and Fixing Screws

Important:


cover straps and accessories.

Extra Information

Pack Quantity Each

The orientation of the trunking is determined by the top compartment.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk