

Product Code:	Product Range:	Issue Date:
TDA62FBD/B	Dado Trunking, Perimeter Trunking	22/8/2025
Description:		
150mm x 60mm Square Da 2 Compartment	do 90° Flat Bend (Downwards) -	
Features:		
8	of multi compartment steel	
norimator trunking	available in both square dado and	

dimension

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk

Important:

cover straps and accessories.

finish for that more industrial look if required or where on-site coating is required
Powder coating is low smoke zero halogen
All Dado and Skirting trunking lengths are supplied complete with lid, joint covers and fixing screws
Earth links are not included and should be ordered separately

 The powder coating not only offers an attractive finish but is also highly resilient to damage during use and

• The lid is also available in a self-colour galvanised

compartment which offers the end user a quick and

 This range combines excellent screening capability and clean design with superior mechanical strength.

The dividers are provided with 20mm knock-outs every 100mm for easy access between partitions
All surface lid are supplied powder coated black to RAL 9005 but a wide variety of colours are available

• Our system has been specifically designed for durability and the ease of installation

making it the ideal solution for high traffic environments such as hospitals, laboratories and

Compliance: Cat6a

easy to fit system

universities

installation.

for that high quality finish.

Technical:

Product Type Flat Bend

Depth 60mm Height 150mm Weight 1.52 Kgs Angle 90Ű Number of Compartments Gauge 1.0mm Material Pre-Galvanised Steel (Zinc Coated) Colour/Finish Black (RAL 9005) Standards BS EN 10346:2015 Compliance Category 6a Supplied With Bridge and Fixing Screws

Pack Quantity Each

Extra Information

The orientation of the trunking is determined by the top compartment.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.