

Product Code:	Product Range:	Issue Date:
TDA62FBD/G	Dado Trunking, Perimeter Trunking	22/8/2025
Description:		
150mm x 60mm Square Dad 2 Compartment	o 90° Flat Bend (Downwards) -	
Features:		
perimeter trunking a chamfered skirting p	of multi compartment steel vailable in both square dado and rofiles available in 2 and 3 offers the end user a quick and	

dimension

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk

Important:

cover straps and accessories.

Technical:Product Type Flat BendDepth 60mmHeight 150mmWeight 1.52 KgsAngle 90°Number of CompartmentsGauge 1.0mmMaterial Pre-Galvanised Steel (Zinc Coated)Colour/Finish Self ColourStandards BS EN 10346:2015Compliance Category 6a

Supplied With Bridge and Fixing Screws

easy to fit system

universities

installation.

separatelyCompliance: Cat6a

on-site coating is required

finish.

• Our system has been specifically designed for durability and the ease of installation

making it the ideal solution for high traffic environments such as hospitals, laboratories and

 This range combines excellent screening capability and clean design with superior mechanical strength.

The dividers are provided with 20mm knock-outs every 100mm for easy access between partitions
All surface lid are supplied self colour but a wide variety of colours are available for that high quality

 The powder coating not only offers an attractive finish but is also highly resilient to damage during use and

• The lid is also available in a self-colour galvanised finish for that more industrial look if required or where

Powder coating is low smoke zero halogen
All Dado and Skirting trunking lengths are supplied complete with lid, joint covers and fixing screws
Earth links are not included and should be ordered

Pack Quantity Each

Extra Information

The orientation of the trunking is determined by the top compartment.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.