



# Tamlex Data Sheet

Product Code:	Product Range:	Issue Date:
TDA62TDL/G	Dado Trunking, Perimeter Trunking	22/8/2025

## Description:

150mm x 60mm Square Dado Flat Tee (Left Down) - 2 Compartment

## Features:

- An extensive range of multi compartment steel perimeter trunking available in both square dado and chamfered skirting profiles available in 2 and 3 compartment which offers the end user a quick and easy to fit system
- Our system has been specifically designed for durability and the ease of installation
- This range combines excellent screening capability and clean design with superior mechanical strength, making it the ideal solution for high traffic environments such as hospitals, laboratories and universities
- The dividers are provided with 20mm knock-outs every 100mm for easy access between partitions
- All surface lid are supplied self colour but a wide variety of colours are available for that high quality finish.
- The powder coating not only offers an attractive finish but is also highly resilient to damage during use and installation.
- The lid is also available in a self-colour galvanised finish for that more industrial look if required or where on-site coating is required
- Powder coating is low smoke zero halogen
- All Dado and Skirting trunking lengths are supplied complete with lid, joint covers and fixing screws
- Earth links are not included and should be ordered separately
- Compliance: Cat6a

## Technical:

**Product Type** Flat Tee

**Depth** 60mm

**Height** 150mm

**Weight** 1.78 Kgs

**Number of Compartments**

**Gauge** 1.0mm

**Material** Pre-Galvanised Steel (Zinc Coated)

**Colour/Finish** Self Colour

**Standards** BS EN 10346:2015

**Compliance** Category 6a

**Supplied With** Bridge and Fixing Screws

**Pack Quantity** Each

## Important:

cover straps and accessories.

## Extra Information

The orientation of the trunking is determined by the top compartment.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

dimension