

# amlex Data Sheet

Product Code: Product Range:

MRE62 Cable Trunking, Standar

Cable Trunking, Standard Trunking

17/9/2025

**Issue Date:** 

**Description:** 

150mm x 50mm Galvanised Steel Trunking (3m Length)

### Features:

- · Single Compartment.
- Manufactured from continuously hot dipped zinc coated low Carbon Steel Strip to BSEN10346: 2015.
- All lid fixings and couplers are included as standard.
- Lid is secured using 'Bridge Pieces'.
- Four lid fixings per 3m length. Bridge pieces also act as cable retainers.
- Multi Compartment trunking and accessories available.
- Special sizes and bespoke designs are available upon request.
- Tamperproof lid fixing option available on request.
- Can be powder coated to customer specific RAL colour.
- Manufactured to allow retrofit installation of our IP4X system. (Sold Separately).



Image for illustrative purposes only

### Technical:

Product Type Trunking

Width 150mm

Height 50mm

Length 3000mm

Weight 8.97 Kgs

Number of Compartments

Material Pre-Galvanised Steel (Zinc Coated)

Colour/Finish Self Colour

Standards BS EN 50085-2-1 2006; BS EN 10346:2015

Supplied With Lid fixings and couplers included.

## Important:

Cable trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.

# **Trunking Weights:**

 1. Compartment
 2. Compartment
 3. Compartment

 8.97 Kgs
 12.599 Kg
 14.283 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

# Dimensions: (mm)


**H** 52mm

**W** 152mm

L 3000mm

**P1** N/A

**P2** 1350mm



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk