



Tamlex Data Sheet

Product Code:	Product Range:	Issue Date:
---------------	----------------	-------------

TSK82IB/G	Perimeter Trunking, Skirting Trunking	22/8/2025
-----------	--	-----------

Description:

200mm x 60mm Chamfered Skirting 90° Internal Bend - 2
Compartment

- Features:**
- An extensive range of multi compartment steel perimeter trunking available in both square dado and chamfered skirting profiles available in 2 and 3 compartment which offers the end user a quick and easy to fit system
 - Our system has been specifically designed for durability and the ease of installation
 - This range combines excellent screening capability and clean design with superior mechanical strength, making it the ideal solution for high traffic environments such as hospitals, laboratories and universities
 - The dividers are provided with 20mm knock-outs every 100mm for easy access between partitions
 - All surface lid are supplied self colour but a wide variety of colours are available for that high quality finish.
 - The powder coating not only offers an attractive finish but is also highly resilient to damage during use and installation.
 - The lid is also available in a self-colour galvanised finish for that more industrial look if required or where on-site coating is required
 - Powder coating is low smoke zero halogen
 - All Dado and Skirting trunking lengths are supplied complete with lid, joint covers and fixing screws
 - Earth links are not included and should be ordered separately
 - Compliance: Cat6a

Technical:	
Product Type	Internal Bend
Depth	60mm
Height	200mm
Weight	3.03 Kgs
Angle	90°
Number of Compartments	
Gauge	1.0mm
Material	Pre-Galvanised Steel (Zinc Coated)
Colour/Finish	Self Colour
Standards	BS EN 10346:2015
Compliance	Category 6a
Supplied With	Bridge and Fixing Screws
Pack Quantity	Each

Important:
cover straps and accessories.

Extra Information

The orientation of the trunking is determined by the top compartment.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

dimension