

Product Code:

Product Range: Perimeter Trunking, Dado Trunking **Issue Date:** 14/9/2025

Description:

TDA83/B

200mm x 60mm Square Dado Trunking - Cat6a 3 Compartment (2m Length)

Features:

- The Tamlex perimeter trunking system offers the end user a quick and easy to fit system.
- This range combines excellent screening capability and clean design with superior mechanical strength, making it the ideal solution for high traffic environments such as hospitals, laboratories and universities whilst also offering first class fire protection.
- All metal construction for maximum strength and durability.
- All partitions have 20mm knock outs ? for ease of installation.
- All surface lid are supplied powder coated black to RAL 9005 but a wide variety of colours are available for that high quality finish.
- The powder coating not only offers an attractive finish but is also highly resilient to damage during use and installation.
- The lid is also available in a self-colour galvanised finish for that more industrial look if required or where on-site coating is required
- Powder coating is low smoke zero halogen
- Full range of accessories Cat6a

Technical:

Important:

cover straps and accessories.

Product Type Trunking
Depth 60mm
Height 200mm
Length 2000mm
Weight 13.16 Kgs
Number of Compartments
Gauge 1.0mm
Material Pre-Galvanised Steel (Zinc Coated)
Colour/Finish Black (RAL 9005)
Standards BS EN 10346:2015
Compliance Category 6a
Supplied With 1x Joint Cover and Fixing Screws
Pack Quantity Length

Extra Information


The orientation of the trunking is determined by the top compartment.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk



Tamlex Data Shee



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk