



Product Code:

Product Range:

Modular Screed Trunking

Description:

FSM350/65/3

3 Compartment 350x65mm Modular Flush Screed Trunking (2M Length)

Features:

- 3 segregated compartments.
- 65mm deep trunking profile.
- Reinforced lid to allow foot traffic.
- · Service boxes can be fitted after trunking is installed, simply by removing trunking lid.
- Service boxes can be positioned/repositioned anywhere along trunking.
- Manufactured from continuously hot dipped zinc coated low Carbon Steel Strip to BSEN 10346:2009.
- · Fillets have rubber gasket strip fitted to increase stability and reduce lid deflection.
- · Modular screed trunking must be installed on a solid foundation and completely supported by a screed ribbon..
- This innovative and customisable system can be installed in new developments or in an existing installation.



Depth 65mm

Width 350mm

Material Pre-Galvanised Steel (Zinc Coated)

Finish Self Colour

Product Type Floor Trunking

Standard BS EN 10346:2009

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.



Issue Date:

15/4/2025



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk