

**Product Code:**

FSM350/65/3

Product Range:

Modular Screed Trunking

Issue Date:

11/8/2025

Description:

3 Compartment 350x65mm Modular Flush Screed Trunking
(2M Length)

Features:

- 3 Segregated Compartments.
- 65mm deep trunking profile.
- Reinforced lid to allow foot traffic.
- Service boxes can be fitted after trunking is installed, simply by removing trunking lid.
- Service boxes can be positioned/repositioned anywhere along trunking.
- Manufactured from zinc galvanised steel strip to BS EN 10346:2015.
- Fillets have rubber gasket strip fitted to increase stability and reduce lid deflection.
- **Modular screed trunking must be installed on a solid foundation and completely supported by a screed ribbon..**
- This innovative and customisable system can be installed in new developments or in an existing installation.

**Technical:****Product Type** Flush Screed Floor Trunking**Width** 350mm**Length** 2000mm**Weight** 27.20 Kgs**Dimensions** 130mm x 85mm x 130mm**Number of Compartments****Material** Pre-Galvanised Steel (Zinc Coated)**Colour/Finish** Self Colour**Standards** BS EN 10346:2015

Supplied With Supplied in standard 2m lengths with 2 x 0.5m lid sections 1 x 1.0m lid section and joining coupler. Rubber grommet supplied to be site fitted.

Important:

Screed trunking must be installed on a solid foundation and completely supported across its complete width by a screed ribbon.

Extra Information

The galvanised trunking lids and service boxes should be in position before the screed is poured to ensure the pressure of the screed does not distort the side walls of the trunking.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.