

Product Code:

Product Range:

ict ivalige.

Modular Screed Trunking

Description:

FSM350/65/3

3 Compartment 350x65mm Modular Flush Screed Trunking (2M Length)

Features:

- 3 Segregated Compartments.
- 65mm deep trunking profile.
- Reinforced lid to allow foot traffic.
- Service boxes can be fitted after trunking is installed, simply by removing trunking lid.
- Service boxes can be positioned/repositioned anywhere along trunking.
- Manufactured from zinc galvanised steel strip to BS EN 10346:2015.
- Fillets have rubber gasket strip fitted to increase stability and reduce lid deflection.
- Modular screed trunking must be installed on a solid foundation and completely supported by a screed ribbon.
- This innovative and customisable system can be installed in new developments or in an existing installation.



Technical:

Product Type Flush Screed Floor Trunking

Width 350mm

Length 2000mm Weight 27.20 Kgs

Dimensions 130mm x 85mm x 130mm

Number of Compartments

Material Pre-Galvanised Steel (Zinc Coated)

Colour/Finish Self Colour

Standards BS EN 10346:2015

Supplied With Supplied in standard 2m lengths with 2 x 0.5m lid sections 1 x 1.0m lid section and joining coupler. Rubber grommet supplied to be site fitted.

Important:

Issue Date:

Screed trunking must be installed on a solid foundation and completely supported across its complete width by a screed ribbon.

Extra Information

The galvanised trunking lids and service boxes should be in position before the screed is poured to ensure the pressure of the screed does not distort the side walls of the trunking.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk