

O

Product Range:

Issue Date: 16/8/2025

Service Boxes, 3 Compartment Boxes

Description:

FSB3/S

3 Compartment 68mm Deep Screed Service Box

Features:

- 3 Compartment Screed Service Box.
- 20mm Knockouts for use with 20mm conduit.
- Reversible self-closing lid.
- Reinforced with steel plates with a recessed lid to allow 10mm infill.
- Durable polycarbonate trim and lid as standard.
- Cable outlets with sponge foam to prevent ingress.
- Floor Cut-out size: 305mm x 205mm.
- Accepts standard 85mm plates only.
- Alternative metal trims available designed specifically for high traffic environments such as receptions and universities. (Can be powder coated).
- Service boxes are designed for use in office type environments and should not be installed in main walkways, corridors, gangways.
- Not suitable for wheeled traffic areas.
- Customer Notice 68mm depth service boxes have restrictive cable capacity.
- The 68mm cavity and screeded service boxes should only be fitted with flush / panel mounted sockets (C2GS) due to the limited depth.

Technical:

Product Type Screed Floor Box

Width 225mm

Depth 68mm

Length 320mm

Weight 3.20 Kgs

Dimensions Overall Size: (L) 320mm x (W) 225mm Floor Cut-Out Size: (L) $305mm \times (W) 205mm$

Number of Compartments

Material Pre-Galvanised Steel (Zinc Coated) / Polycarbonate

Colour/Finish Self Colour

Supplied With 20mm Knockout Only

Extra Information

only flush or panel-mounted sockets (C2GS) should be used.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.



Important:

68mm deep service boxes have limited cable capacity.