

Product Code:

Product Range:
Flush Screed Trunking

Issue Date:

29/3/2025

FSB3

Description:

3 Compartment 68mm Service Box for 225x25mm Flush Screed Trunking

Features:

- 3 Compartment Flush Screed Service Box.
- Reversible self-closing lid.
- Reinforced with steel plates with a recessed lid to allow 10mm infill.
- Durable polycarbonate trim and lid as standard.
- Cable outlets with sponge foam to prevent ingress.
- Service boxes are designed for use in office type environments and should not be installed in main walkways, corridors, gangways or in contact with wheeled traffic.
- The minimum screed depth is 68mm. Service boxes should be installed when the trunking is fitted.
- Screed trunking must be installed on a solid foundation and completely supported by a screed ribbon..
- Suitable for Tamlex flush screed trunking only.



Technical:

Depth 69mm
Width 225mm
Material Pre-Galvanised Steel (Zinc Coated)
Finish Self Colour
Trunking Type Floor Trunking

Standard BS EN 10346:2009

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk