

# **amlex** Data Sheet

# **Product Code:**

# Product Range:

# Issue Date:

1/6/2025



Turnbuckle Accessories, Cable 1/6/2 Trunking

# Description:

TGHN128

300mm x 200mm 45° IP4X Turnbuckle Gusset Bend Inside Lid

# Features:

- Tamlex offers a comprehensive range of gusset bends and tees which allow a greater bend radius for cables.
- Intergrated IP4X compliance as standard no need to order additional components.
- All bends are supplied with built-in threaded couplers to allow them to be fitted directly to the trunking using an M6 screw.
- All lids are secured using a turnbuckle fixing.
- Multi Compartment trunking and accessories available.
- Special sizes and bespoke designs are available upon request.
- Tamperproof lid fixing option available on request.
- Can be powder coated to customer specific RAL colour.

## **Technical:**

| Product Type Gusset Bend                    |  |  |
|---|--|--|
| Width 300mm                                 |  |  |
| Height 200mm                                |  |  |
| Angle 45°                                   |  |  |
| Number of Compartments                      |  |  |
| Material Pre-Galvanised Steel (Zinc Coated) |  |  |
| Colour/Finish Self Colour                   |  |  |
| Standards BS EN 50085-2-1 2006; BS EN 10346 |  |  |

### **Trunking Weights:**


| 1. Compartment | 2. Compartment | 3. Compartment |
|----------------|----------------|----------------|
| 1.401 Kg       | 1.650 Kg       | 1.899 Kg       |


The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

### Dimensions: (mm)

H 202mm W 298mm L 234mm

**P1** 87mm





Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk



IMAGE FOR ILLUSTRATIVE PURPOSES ONLY

### Important:

Cable trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.