



Product Code: Product Range:

Cable Trunking, Turnbuckle Trunking





Description:

TRE22

50mm x 50mm Turnbuckle Galvanised Steel Trunking (3m Length)

Features:

- · Single Compartment.
- Turnbuckle lid fixing for speed and convenience.
- · Manufactured from zinc galvanised steel strip to BSEN10346: 2009.
- 4 or 8 lid fixing per 3m length.
- · All lid fixings and couplers are included as standard.
- Multi Compartment trunking and accessories available.
- Special sizes and bespoke designs are available upon request.
- Tamperproof lid fixing option available on request.
- · Can be powder coated to customer specific RAL colour.
- IP4X Cover straps are only required for Length to Length joins. (Sold Separately).



_								
	Δ	r	h	n	10	a	ı	•
	◡	·			10	·u		

Depth 50mm

Width 50mm

Length 50mm

Material BS EN 10346 Steel

Finish Pre Galvanised Steel (Zinc Coated)

Trunking Type Trunking

Standard BS EN 50085-2-1 2006; BS EN 10346

Supplied With Turnbuckle lid fixings and coupler included.

Important:

Cable trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.

Extra Information

details must be supplied at the time of order. 3 compartment is available in width code 3 and above., Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments


Trunking Weights:

1. Compartment	2. Compartment	3. Compartment
4.981 Kg	6.665 Kg	N/A

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions: (mm)

H 52 mm W 52 mm L 3000 mm **P1** N/A P2 1350 mm



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER

T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk