



Tamlex Data Sheet

Product Code:	Product Range:	Issue Date:																		
REL3S	Security Trunking, Cable Trunking	26/7/2025																		
Description:																				
75mm Security Galvanised Steel Trunking Lid																				
Features:																				
<ul style="list-style-type: none">• Spare Galvanised Steel Trunking Lid.• Supplied with Security fixings.																				
Technical:																				
<table><tr><td>Product Type</td><td>Lid</td></tr><tr><td>Width</td><td>75mm</td></tr><tr><td>Height</td><td>10mm</td></tr><tr><td>Length</td><td>2000mm</td></tr><tr><td>Material</td><td>Pre-Galvanised Steel (Zinc Coated)</td></tr><tr><td>Colour/Finish</td><td>Self Colour</td></tr><tr><td>Standards</td><td>BS EN 50085-2-1 2006; BS EN 10346:2015</td></tr><tr><td>Compliance</td><td>STD/E/SPEC/018</td></tr><tr><td>Supplied With</td><td>Turnbuckle lid fixings</td></tr></table>			Product Type	Lid	Width	75mm	Height	10mm	Length	2000mm	Material	Pre-Galvanised Steel (Zinc Coated)	Colour/Finish	Self Colour	Standards	BS EN 50085-2-1 2006; BS EN 10346:2015	Compliance	STD/E/SPEC/018	Supplied With	Turnbuckle lid fixings
Product Type	Lid																			
Width	75mm																			
Height	10mm																			
Length	2000mm																			
Material	Pre-Galvanised Steel (Zinc Coated)																			
Colour/Finish	Self Colour																			
Standards	BS EN 50085-2-1 2006; BS EN 10346:2015																			
Compliance	STD/E/SPEC/018																			
Supplied With	Turnbuckle lid fixings																			
Important:																				
Tamlex cable trunking is designed for maximum strength and durability in mind. It should be installed so that the lid does not support cable weight. Incorrect installation may compromise the integrity of the system and is not recommended., with the main cable engineered to support the weight of the cables. To ensure optimal performance and safety																				

Important:

Tamlex cable trunking is designed with strength and durability in mind, trunking must be installed so that the lid does not bear any cable weight. Incorrect installation may affect the integrity of the system and is not recommended., with the main body engineered to support the weight of installed cables. To ensure optimal performance and safety

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.