

Tamlex Data Sheet

Product Code:

MDL/900/G

Hot Dipped Galvanised, Ladder, 31/8/2025 Medium Duty

Product Range:

Description:

900mm Medium Duty 100mm Deep Ladder HDG - 3 Metre Length

Features:

- Durable hot dip galvanised finish for long-term corrosion resistance.
- Designed to support high cable loads over long spans.
- Suitable for heavy-duty industrial and commercial applications.
- Wide range of accessories including bends, tees, risers and reducers.
- Compatible with industry-standard fixings and couplers.
- Rung spacing: 300mm between centres.
- Even when ladders are cut to length, the slots in the coupler will always align with the slots in the ladder side rails.
- When connecting fittings to straight lengths, use fastener sets.
- Manufactured to meet UK and international standards.
- Covers for cable ladder available upon request.
- 6 metre lengths available upon request.

Technical:

Product Type Ladder Tray

Width 900mm

Height 100mm

Length 3000mm

Weight 22.20 Kgs

Dimensions 300mm Rung Pitch

Gauge 1.5mm

Material Post Hot-Dipped Galvanised (HDG)

Colour/Finish Self Colour

Standards BS EN ISO 1461:2009

Extra Information

3 m and 4 m spans using 3 m lengths. Safe working load should include all cable loads and any other additional loads (e.g. wind, snow).

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions: (mm)

W 940mm



Image for illustrative purposes only

Important:

Issue Date:

HDG ladders are suitable for internal and external use, including light industrial and coastal environments. Ensure cut edges or drilled holes are treated with a suitable zincrich paint or similar to maintain corrosion protection.