



Product Code:	Product Range:	Issue Date:
LD/ECC	Accessories, Hot Dipped Galvanised, Ladder	1/7/2025

Description:
Earth Braid Continuity Connector (320mm) For Ladder

- Features:**
- If a supplementary bonding conductor for equipotential earthing is required, straight lengths and fittings in all Tamlex ladder ranges have fixing holes provided to accommodate a flexible earth continuity connector.
 - On straight lengths, fixing holes are pitched every 75mm to avoid the need for drilling if the ladder is cut.
 - The earth continuity connector has a current capacity rating of 100 Amps.
 - Supplied in quantities of ten with fasteners.

Technical:	
Product Type	Accessories
Width	18mm
Length	320mm
Weight	0.01 Kgs
Gauge	2.0mm
Material	Tinned Copper
Colour/Finish	Self Colour
Standards	BS EN ISO 1461:2009
Supplied With	2x M6 Brass Fastener Sets Per Connector
Pack Quantity	10 Per Pack

Important:
HDG ladders are suitable for internal and external use, including light industrial and coastal environments. Ensure cut edges or drilled holes are treated with a suitable zinc-rich paint or similar to maintain corrosion protection.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.