

**Product Code:**

LD/ECC

Product Range:Accessories, Hot Dipped
Galvanised, Ladder**Issue Date:**

31/8/2025

Description:

Earth Braid Continuity Connector (320mm) For Ladder

Features:

- If a supplementary bonding conductor for equipotential earthing is required, straight lengths and fittings in all Tamlex ladder ranges have fixing holes provided to accommodate a flexible earth continuity connector.
- On straight lengths, fixing holes are pitched every 75mm to avoid the need for drilling if the ladder is cut.
- The earth continuity connector has a current capacity rating of 100 Amps.
- Supplied in quantities of ten with fasteners.

**Technical:****Product Type** Accessories**Width** 18mm**Length** 320mm**Weight** 0.01 Kgs**Gauge** 2.0mm**Material** Tinned Copper**Colour/Finish** Self Colour**Standards** BS EN ISO 1461:2009**Supplied With** 2x M6 Brass Fastener Sets Per Connector**Pack Quantity** 10 Per Pack**Important:**

HDG ladders are suitable for internal and external use, including light industrial and coastal environments. Ensure cut edges or drilled holes are treated with a suitable zinc-rich paint or similar to maintain corrosion protection.

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.