



**Product Code:**

TSK6TSS

**Product Range**

Skirting Trunking Accessory

**Issue Number:**

A

**Issue Date:**

22/07/2021

# Tamlex Data Sheet

**Description:**

150 mm x 60 mm Chamfered Skirting 2 Gang Switched Socket Plate

**Features:**

- Available in square dado and chamfered skirting
- Suitable for 2 compartments
- Ideal solution for high traffic environments such as hospitals, laboratories and universities
- Socket positioned for main compartment
- Wide variety of colours are available for that high quality finish
- Supplied complete with lid and fixing screws
- Lid designed to fit over trunking lid to provide an IP4X compliant seal. (No additional joint covers required)



**Technical:**

<b>Height</b>	150 mm
<b>Depth</b>	60 mm
<b>Length</b>	250 mm
<b>Material</b>	Pre-Galvanised Steel
<b>Finish</b>	Powder Coated White RAL 9016
<b>Colour</b>	White
<b>Trunking Type</b>	Perimeter Skirting Trunking Accessory
<b>Standard</b>	BS EN 10346
<b>Guarantee</b>	1 Year
<b>Weight</b>	0.75 kg
<b>Current Rating</b>	13 A
<b>Switched/Unswitched</b>	Switched
<b>Frequency</b>	50 Hz

**Important:**

Trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.

Ensure clearance between trunking body and floor finish is allowed for fitment of lid, cover straps and accessories.

**Dimensions:**

