

Product Code:	Issue Number:	Issue Date:	Issued By:	IP4X
TGBT22	2.0	18/11/2022	ADH	GERTIFIED

Description:

50X50 IP4X 90° GUSSET BEND TOP LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



ERTIFI

Important:

Cable trunking is designed such that the nain body carries the weight of cables. Frunking should NOT be installed in any vay that causes the lid to carry the cable veight.

Technical:

		Ca
Height	50 mm	ma
Width	50 mm	Tru wa
Length	141 mm	we
Material	0.9 mm steel	
Finish	Pre-Galvanised Steel	
Trunking Type	Turnbuckle Gusset Bend	
Standard	BS EN 50085-1; BS EN 10346	
IP Rating	IP4X	

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

Weights:

1 Compartment	2 Compartment	3 Compartment
0.181 Kg	0.236 Kg	N/A

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions: mm

Н	52 mm
W	141 mm
D	48 mm
P1	25 mm
P2	N/A Single hole

Dimensions are identical for single and multi-compartment

