

| Product Code: | Issue Number: | Issue Date: | Issued By: |
|---------------|---------------|-------------|------------|
| | | | |





Description:

100X75 IP4X 90° GUSSET BEND TOP LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Important:

Technical:

| recrimical: | | Cable trunking is designed such that the |
|---------------|----------------------------|--|
| Height | 75 mm | main body carries the weight of cables. |
| Width | 100 mm | Trunking should NOT be installed in any way that causes the lid to carry the cable |
| Length | 211 mm | weight. |
| Material | 1.0 mm steel | |
| Finish | Pre-Galvanised Steel | |
| Trunking Type | Turnbuckle Gusset Bend | |
| Standard | BS EN 50085-1; BS EN 10346 | |
| IP Rating | IP4X | |

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.


Weights:


| 1 Compartment | 2 Compartment | 3 Compartment |
|---------------|---------------|---------------|
| 0.451 Kg | 0.532 Kg | 0.613 Kg |

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

| Dimensions: | mm |
|-------------|--------|
| Н | 77 mm |
| W | 211 mm |
| D | 98 mm |
| P1 | 55 mm |
| P2 | 20 mm |

Dimensions are identical for single and multi-compartment





Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk