

Product Code: Issue Number: Issue Date: Issued By:

2.0 21/11/2022



Description:

TGFT62

150X50 IP4X GUSSET FOURWAY

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



ADH

Technical:

Height	50 mm		
Width	150 mm		
Length	200 mm	,	
Material	1.0 mm steel		
Finish	Pre-Galvanised Steel		
Trunking Type	Turnbuckle Gusset Bend		
Standard	BS EN 50085-1; BS EN 1034	BS EN 50085-1; BS EN 1034	
IP Rating	IP4X		

Important:

Cable trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.

Multi-Compartment Options


Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

Weights:


1 Compartment	2 Compartment	3 Compartment
0.762 Kg	0.952 Kg	1.142 Kg


The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	148 mm
W	148 mm
D	52 mm
P1	N/A Single hole



Dimensions are identical for single and multi-compartment





Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk