

Product Code:	Issue Number:	Issue Date:	Issued By:
Todact oodc.	133de Hullibel.	issue Date.	issued by.

22/11/2022

ADH

IP4X

**Description:** 

TGHN82

200X50 IP4X 45° GUSSET BEND INSIDE LID

2.0

## Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Important:

Cable trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.

Technical:		
Height	50 mm	
Width	200 mm	
Length	114 mm	
Material	1.0 mm steel	
Finish	Pre-Galvanised Steel	
Trunking Type	Turnbuckle Gusset Bend	
Standard	BS EN 50085-1; BS EN 10346	
IP Rating	IP4X	

## **Multi-Compartment Options**

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.


## Weights:


1 Compartment	2 Compartment	3 Compartment	
0.371 Kg	0.426 Ka	0.481 Ka	

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	52 mm
W	198 mm
D	52 mm
L	114 mm
P1	N/A Single hole

Dimensions are identical for single and multi-compartment





**(** 

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk