

Product Code:	Issue Number:	Issue Date:	Issued By:	(P
TGHO82	2.0	23/11/2022	ADH	CERT

Description:

200X50 IP4X 45° GUSSET BEND OUTSIDE LID

Features:

Technical:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Important: Cable trunking is designed such that the

Height	50 mm	main body carries the weight of cables.	
Width	200 mm	Trunking should NOT be installed in any way that causes the lid to carry the cable	
Length	114 mm	weight.	
Material	1.0 mm steel		
Finish	Pre-Galvanised Steel		
Trunking Type	Turnbuckle Gusset Bend		
Standard	BS EN 50085-1; BS EN 10346		
IP Rating	IP4X		

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.


Weights:

1 Compartment	2 Compartment	3 Compartment
0.371 Kg	0.426 Kg	0.481 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	52 mm
W	198 mm
D	52 mm
L	114 mm
I	35 mm
P1	N/A Single hole

Dimensions are identical for single and multi-compartment



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk