

Product Code:	Issue Number:	Issue Date:	Issued By:	IP4X
TGHT93	2.0	24/11/2022	ADH	CERTIFIED

Description:

225X75 IP4X 45° GUSSET BEND TOP LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



RTIF

Important:

Cable trunking is designed such that the nain body carries the weight of cables. Trunking should NOT be installed in any vay that causes the lid to carry the cable veight.

Technical:

		Ca
Height	75 mm	ma
Width	225 mm	Tru wa
Length	219 mm	we
Material	1.0 mm steel	
Finish	Pre-Galvanised Steel	
Trunking Type	Turnbuckle Gusset Bend	
Standard	BS EN 50085-1; BS EN 10346	
IP Rating	IP4X	

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

Weights:


1 Compartment	2 Compartment	3 Compartment
0.884 Kg	0.965 Kg	1.046 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions: mm

н	77 mm
W	219 mm
D	223 mm
P1	55 mm
P2	20 mm

Dimensions are identical for single and multi-compartment



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk