

Product Code:	Issue Number:	Issue Date:	Issued By:	ĨΡ
TGTN88	20	25/11/2022	ADH	CERT

Description:

200X200 IP4X GUSSET TEE INSIDE LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Important: Technical: Cable trunking is designed such that the 200 mm Height main body carries the weight of cables. Trunking should NOT be installed in any 200 mm Width way that causes the lid to carry the cable 250 mm Length weight. 1.0 mm steel Material Finish Pre-Galvanised Steel Turnbuckle Gusset Bend **Trunking Type** BS EN 50085-1; BS EN 10346 Standard

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

IP4X

Weights:


IP Rating


1 Compartment	2 Compartment	3 Compartment
1.867 Kg	2.331 Kg	2.795 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	198 mm
W	202 mm
D	225 mm
L	198 mm
P1	87 mm

198 mm 87 mm





Dimensions are identical for single and multi-compartment

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk