

Product Code:	Issue Number:	Issue Date:	Issued By:
TGTN99	2.0	25/11/2022	ADH

# **Description:**

# 225X225 IP4X GUSSET TEE INSIDE LID

## Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



#### Important: Technical: Cable trunking is designed such that the 225 mm Height main body carries the weight of cables. Trunking should NOT be installed in any 225 mm Width way that causes the lid to carry the cable 275 mm Length weight. 1.0 mm steel Material Finish Pre-Galvanised Steel Turnbuckle Gusset Bend **Trunking Type** BS EN 50085-1; BS EN 10346 Standard

**Multi-Compartment Options** 

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

IP4X


## Weights:

**IP Rating** 


1 Compartment	2 Compartment	3 Compartment
2.237 Kg	2.804 Kg	3.371 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	223 mm
W	227 mm
D	250 mm
L	223 mm
P1	87 mm



Dimensions are identical for single and multi-compartment



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk