

Product Code:	Issue Number:	Issue Date:	Issued By:

09/01/2023 **ADH**

Description:

TNEN123

300X75 IP4X 90° SHARP BEND INSIDE LID

2.0

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Technical:

Height	75 mm	
Width	300 mm	
Length	115 mm	
Material	1.0 mm steel	
Finish	Pre-Galvanised Steel	
Trunking Type	Turnbuckle Sharp Bend	
Standard	BS EN 50085-1; BS EN 10346	
IP Rating	IP4X	

Important:

Cable trunking is designed such that the main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable weight.

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.


Weights:

	<u> </u>		
1 Compartment	2 Compartment	3 Compartment	
1.069 Kg	1.165 Kg	1.261 Ka	_

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	77 mm
W	298 mm
D	137 mm
L	163 mm
I	56 mm
P1	35 mm

Dimensions are identical for single and multi-compartment



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk