

## **Description:**

# 100X100 IP4X 90° SHARP BEND TOP LID

#### Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



#### Important:

Cable trunking is designed such that the ain body carries the weight of cables. unking should NOT be installed in any ay that causes the lid to carry the cable eight.

#### Technical:

		Ca
Height	100 mm	ma
Width	100 mm	Tru wa
Length	140 mm	we
Material	1.0 mm steel	
Finish	Pre-Galvanised Steel	
Trunking Type	Turnbuckle Sharp Bend	
Standard	BS EN 50085-1; BS EN 10346	
IP Rating	IP4X	

### **Multi-Compartment Options**

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

#### Weights:

1 Compartment	2 Compartment	3 Compartment
0.742 Kg	0.890 Kg	1.038 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm			-		
Н	102 mm	_				
W	98 mm	3				
D	172 mm	_				
L	198 mm	- <u>.</u>			$+$ $\wedge$	
I	56 mm	_	-	L	_	
P1	50 mm			-		
Dimensions are ide single and multi-co		T				

Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk