

Product Code:	Issue Number:	Issue Date:	Issued By:	(ip
TNET63	2.0	05/01/2023	ADH	CERT

## **Description:**

150X75 IP4X 90° SHARP BEND TOP LID

## Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



## **Important:** Technical: Cable trunking is designed such that the 75 mm Height main body carries the weight of cables. Trunking should NOT be installed in any 150 mm Width way that causes the lid to carry the cable 190 mm Length weight. 1.0 mm steel Material Finish Pre-Galvanised Steel Turnbuckle Sharp Bend **Trunking Type** BS EN 50085-1; BS EN 10346 Standard

**Multi-Compartment Options** 

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

IP4X

## Weights:


**IP Rating** 

1 Compartment	2 Compartment	3 Compartment
1.014 Kg	1.156 Kg	1.298 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	77 mm
W	148 mm
D	242 mm
L	268 mm
I	56 mm
P1	35 mm

Dimensions are identical for single and multi-compartment



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk