

Product Code:	Issue Number:	Issue Date:	Issued By:	Œ
TNET96	2.0	05/01/2023	ADH	CE

Description:

225X150 IP4X 90° SHARP BEND TOP LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Important: Technical: Cable trunking is designed such that the 150 mm Height main body carries the weight of cables. Trunking should NOT be installed in any 225 mm Width way that causes the lid to carry the cable 265 mm Length weight. 1.0 mm steel Material Finish Pre-Galvanised Steel Turnbuckle Sharp Bend **Trunking Type** BS EN 50085-1; BS EN 10346 Standard

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.

IP4X

Weights:


IP Rating

1 Compartment	2 Compartment	3 Compartment
2.157 Kg	2.534 Kg	2.911 Kg

The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	152 mm
W	223 mm
D	347 mm
L	373 mm
I	56 mm
P1	87 mm

Dimensions are identical for single and multi-compartment



Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk