



Product Code:	Issue Number:	Issue Date:	Issued By:	(P
TNTT22	2.0	04/01/2023	ADH	CERT

Description:

50X50 IP4X SHARP TEE TOP LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



Trunking should NOT be installed in any

way that causes the lid to carry the cable

weight.

Technical: Height 50 mm Important: Cable trunking is designed such that the main body carries the weight of cables.

Width 50 mm

Length 130 mm

Material 0.9 mm steel

Finish Pre-Galvanised Steel

Trunking Type Turnbuckle Sharp Bend

Standard BS EN 50085-1; BS EN 10346

IP Rating IP4X

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.


Weights:


1 Compartment	2 Compartment	3 Compartment
0.354 Kg	N/A	N/A


The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	52 mm
W	48 mm
L	130 mm
1	56 mm
P1	N/A Single hole

Dimensions are identical for single and multi-compartment







Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk