

Product Code:	Issue Number:	Issue Date:	Issued By:	IP4)
TNTT88	20	04/01/2023	ADH	CERTIFIE

Description:

200X200 IP4X SHARP TEE TOP LID

Features:

Our IP4X turnbuckle trunking offers a range of gusset bends and tees which allow a greater bend radius for cables.

Designed with built-in couplers on all outlets and an integrated lip which fit inside the trunking body, while the lid is designed to fit over the main trunking lid. Manufactured from continuously hot dipped zinc coated low carbon steel strip to BSEN10346: 2009.



main body carries the weight of cables. Trunking should NOT be installed in any way that causes the lid to carry the cable

weight.

Technical: Important: Cable trunking is designed such that the

Height	200 mm	
Width	200 mm	
Length	280 mm	
Material	1.0 mm steel	
Finish	Pre-Galvanised Steel	
Trunking Type	Turnbuckle Sharp Bend	
Standard	BS EN 50085-1; BS EN 10346	
IP Rating	IP4X	

Multi-Compartment Options

Standard trunking and accessories are available in multi compartment options. Trunking and accessories are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order. 3 compartment is available in width code 3 and above.


Weights:


1 Compartment	2 Compartment	3 Compartment
2.160 Kg	2.984 kg	3.149 kg


The approximate weights given are for pre-galvanised finish only, in kilograms (nominal) and subject to material thickness tolerance.

Dimensions:	mm
Н	202 mm
W	198 mm
L	280 mm
1	56 mm
P1	87 mm

Dimensions are identical for single and multi-compartment







Tamlex | Harcourt | Halesfield 15 | Telford | Shropshire | TF7 4ER T: 01952 586689 E: sales@tamlex.co.uk W: www.tamlex.co.uk